Updates to the PCB Exposure Estimation Tool and Exposure Levels for Evaluating PCBs in Indoor School Air




Linda Phillips, EPA/ORD/NCEA
PCB National Meeting, August 5, 2015

The views expressed in this presentation are those of the author and they do not necessarily reflect the views or policies of the U.S. Environmental Protection Agency or other collaborating agencies

Purpose:

- Developed in 2009 as a simple tool to estimate PCB exposure from school and non-school pathways
- Calculates the maximum school indoor air PCB concentrations (ng/m³) that do not exceed the RfD, considering other school and non-school pathways
- Enables users to input site-specific values and tailor screening limits to local conditions



Exposure Pathways:

Non-school Pathways		School Pathways		
<u>INDOOR</u>	<u>OUTDOOR</u>	INDOOR	<u>OUTDOOR</u>	
Inhalation	Inhalation	Inhalation	Inhalation	
Dust Ingestion	Soil Ingestion	Dust Ingestion	Soil Ingestion	
Dust Contact		Dust Contact	- -	
Diet (fixed value)		-	-	

Key Assumptions:

- Uses RfD for Aroclor 1254 because it provides the most conservative estimates
- Assumes all other school exposure concentrations (e.g., dust, soil, outdoor air) are the same as background
- Uses typical (average) contact rates
- Dietary intake of PCBs based on FDA
 Total Diet Study Data



History:

- Version 1.1
 - Developed in 2009
 - Used FDA dietary data from the 1997 Total Diet Study
 - Formed the basis of the Public Health Levels (PHLs) for Indoor School Air
 - PHLs were posted on EPA PCB website
- Version 1.2
 - Updated Tool in 2010 and revised in 2015
 - Uses FDA dietary data from the 2003 Total Diet Study
 - » Dietary values are lower than in Version 1.1
 - Forms the basis of the updated Exposure Levels for Evaluating (ELEs) Indoor School Air (formerly called PHLs)



ELEs for PCBs in Indoor School Air

- Revised PHL terminology to Exposure Levels for Evaluation (ELEs) of PCBs in Indoor School Air
 - Better reflects intended purpose
 - Should not be interpreted nor applied as "bright line" or "not-to-exceed" criteria
 - May be used to guide thoughtful evaluation of indoor air quality in schools
 - Updated values and terminology posted to website
 http://www.epa.gov/epawaste/hazard/tsd/pcbs/pubs/caulk/exposure levels.htm
- Both PHLs and ELEs represent the maximum school indoor air PCB concentrations (ng/m³) that do not exceed the RfD, considering other school and non-school pathways


ELEs for PCBs in Indoor School Air (ng/m³)

Values based on Version 1.1 and Version 1.2 of Tool

Age group (years)	Version 1.1 (rounded values)	Version 1.2 (rounded values) ¹		
1 to <2	70	100		
2 to <3	70	100		
3 to <6	100	200		
6 to <12	300	300		
12 to <15	450	500		
15 to <19	600	600		
Adult	450	500		

¹ Rounded to one significant figure.

PCB Exposure Estimation Tool & ELEs



Uncertainties and Limitations:

- Used oral RfD for inhalation pathway
- Based on Aroclor 1254
- Some data suggest PCB indoor air profiles may be more similar to Aroclor 1016
- Used generic background and school assumptions
 site specific values are preferable
- Does NOT link PCB exposures to specific PCB sources

Thank you for your attention!



Contact Information

Linda Phillips, ORD/NCEA 703-347-0366; phillips.linda@epa.gov